

abitex

abitex srl
via del cristo 84
33044 manzano
ud - italy

t +39 0432 746060
www.abitex.eu
info@abitex.eu

b-green grs struttura R08217



IT
codice doganale
54071000.

utilizzo
imbottiti, outdoor.

caratteristiche
95% poliestere riciclato - 5% poliestere,
altezza cm $\pm$ 140, peso $\pm$ 580 gr/m².

tintura
il prodotto è tinta in filo.

lunghezza pezze
circa 30 mtl., disponibile anche al taglio con maggiorazione.

abrasione
> 100.000 cicli, ISO 12947-2.

solidità alla luce
6/7, ISO 105 B02.

solidità allo sfregamento
secco 4/5, umido 4, ISO 105 X12.

resistenza alla cucitura
ordito 2 mm, trama 3 mm, ISO 13936-2.

pilling
4/5, ISO 12945-2.

sostenibilità
Oeko-tex®, GRS.

resistenza al fuoco
1IM - UNI 9175; EN 1021 part 1/2; BS 5852 crib 5;
NF-P 92 503 - M1; NFPA 260 - Class 1;
California TB 117:2013; IMO MED 3.20/Ftp 307 part 8.

attenzione
sono ammesse leggere differenze di colore tra differenti
partite. le schede tecniche vengono costantemente
aggiornate sul sito, pertanto vi invitiamo a verificare online i
dati del prodotto su www.abitex.eu

EN
customs code
54071000.

use
upholstered furniture, outdoor.

features
95% recycled polyester - 5% polyester,
width cm $\pm$ 140, weight $\pm$ 580 g/m².

dyeing
yarn dyed product.

roll length
approx. 30 lm, can also be cut-to-length at an extra cost.

abrasion resistance
> 100.000 rubs, ISO 12947-2.

colour fastness to light
6/7, ISO 105 B02.

fastness to rubbing
dry 4/5, wet 4, ISO 105 X12.

seam slippage
warp 2 mm, weft 3 mm, ISO 13936-2.

pilling
4/5, ISO 12945-2.

sustainability
Oeko-tex®, GRS.

fire resistance
1IM - UNI 9175; EN 1021 part 1/2; BS 5852 crib 5;
NF-P 92 503 - M1; NFPA 260 - Class 1;
California TB 117:2013; IMO MED 3.20/Ftp 307 part 8.

attention
slight colour differences between different batches are
allowed. as technical data sheets are updated from time to
time, we invite you to verify the latest document published for
each item on the website www.abitex.eu



fireproof



imo-med



outdoor



recycled



eco-friendly



standard
100



year
guarantee